

11 x GRAND CRU CANOPY

MAGICAL LIGHT INSTALLATIONS WITH CUSTOMISED CANOPIES

Ideal for entrance and reception areas, bathrooms, staircases, waiting areas, dining tables or conference environments. The pendants can be freely combined, distributed, rotated and adjusted to the required heights to make each installation unique. The canopy optionally hides the electronics and serves the purpose of electricity distribution.

Technical specifications

Voltage	24 V DC (CV)
Power	approx. 75 Watts
Luminous flux / efficiency	3,600 lm / 50 lm/W

Colour temperature	2,000–2,700 K
Weight	approx. 30 kg
Dimensions e.g.	Canopy Ø 600 mm

LED modules with various colour temperatures control the colour of the glass (among other things): "Warm white LED": 2,700 K, > 90 Ra; "Amber LED": 2,400 K, > 80 Ra; "Tuneable white LED": 2,000–2,700 K (adjustable colour temperature), approx. 110 Watts, > 80→90 Ra. Can be combined with glass colours: Amethyst, Mandarin Garnet, Peridot, Sapphire, Tourmalin, Turquoise, Citrin, Smoky Quartz, Amber und Rose Quartz. Lifespan of the LED module: approx. 40,000 hours; can be replaced by electrician.

Control technology


The light fixture is dimmable with interface for trailing edge, 1–10 V, pushdim, remote control, or DALI. Dimmer / power supplies can be installed internally or externally; switches / controllers to be provided by the customer.

Ceiling bracket / cable

The ceiling bracket shown is merely an example. Please talk to us about a customised version. Ceiling brackets are available in different diameters. Usually wire-insulated, tin-plated tensile cable with diameter 4.0 mm, standard cable length 2 m, individual cable length up to 20 m.

Material

Please select your preferred surface finish for the socket and ceiling bracket in the "Material" section of our website.



MASSIFCENTRAL

LCB Manufactur GmbH, Mommsenstr. 65, D-10629 Berlin
Phone +49 30 91 44 75 62, info@massifcentral.de, www.massifcentral.de

